



PAN
LIGHTING

PNLN101

LED LinearLight



Introduction

PNLN105 LED Linear light with SMD LED and SMD driver. it is the right choice for many applications. Developed and produced in SAUDI, PAN Lighting has the capabilities and the international connections to make such a product suitable and reliable outdoor fixture for all weather conditions.

Features

- High purity quality extruded aluminium.
- Surface anodized or RAL color system epoxy powder coated UV resistance
- Surface installation
- IP rating: IP20

Data

Model	PNLN101-40	PNLN101-30	PNLN101-20
Power	40W	30W	20W
LED Type	SMD		
Lumious Flux	3800 lm	2850 lm	1900 lm
Efficacy	95 lm/w	95 lm/w	95 lm/w
CCT	3000 K	4000 K	6500 K
CRI (Ra)	>80		
Voltage	240-220 V		
Frequency	60/50 Hz		

PNLN101

LED LinearLight



Specification

Housing	High purity quality extruded aluminium, surface anodized or RAL color system epoxy powder coated UV resistance
Optic	Sanded semi-opal polycarbonate diffuser
Installation	Surface / Suspended
IP Rating	IP40/65
Options	Dimming, Emergency Customized length on request

LED Module

LED Brand	Cree / Lumiled
Efficiency	95 lm/W
CCT	3000k - 4000k - 6500k
CRI	>80
Wiring	Push terminals for quick & simple wiring of LED module to LED module
Long Lifetime	50,000 hours (30,000 hours optional)